



NTN NKX30T2 complex bearings

Bearing No. NKX30T2

NKX30T2 Bearing 2D drawings and 3D CAD models

Bore Diameter	30 mm
Outer Diameter	47 mm
d	30 mm
Fw	30 mm
D	42 mm
D1	47 mm
C	30 mm
r min.	0,6 mm
C1	11 mm
da min.	40 mm
ra max.	0,6 mm
C2	9,5 mm
Weight	0,14 Kg
Dynamic load rating radial (C)	22,3 kN
Dynamic load rating axial (C)	20,4 kN
Static load rating radial (C0)	39,5 kN
Static load rating axial (C0)	42 kN
(Grease) Lubrication Speed	4300 r/min
dw	30 mm
rs min	0.6 mm
Dw	2.5 mm
Dw1	6.35 mm
Lw	15.8 mm
Lubrication hole on outer ring	Oui/Yes



NSK bearing Trading Co., Ltd

Precision class	P0
Mass	0.14 kg
Cr	22.3 kN
Ca	20.4 kN
C0r	39.5 kN
C0a	42 kN
Nlim (grease)	4,300 rpm
Nlim (oil)	6,200 rpm
Min operating temperature, Tmin	-20 ° C
Max operating temperature, Tmax	120 ° C
da min	40 mm
ras max	0.6 mm
Category	Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.144
Product Group	B04144